

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	15	25	98	65	4	14	24	BFS-15-25/25
2	20	25	98	75	4	14	24	BFS-20-25/25
3	25	25	116	85	4	14	24	BFS-25-25/25
4	32	25	140	100	4	18	24	BFS-32-25/25
5	40	25	154	110	4	18	24	BFS-40-25/25
6	50	25	164	125	4	18	24	BFS-50-25/25
7	65	25	184	145	4	18	24	BFS-65-25/25
8	80	25	200	160	8	18	28	BFS-80-25/25
9	100	25	228	190	8	22	28	BFS-100-25/25
10	125	25	270	220	8	26	30	BFS-125-25/25
11	150	20	305	250	8	26	30	BFS-150-20/25
12	150	25	305	250	8	26	35	BFS-150-25/25
13	200	20	380	310	12	26	40	BFS-200-20/25
14	200	25	380	310	12	26	44	BFS-200-25/25
15	250	20	430	370	12	30	44	BFS-250-20/25
16	250	25	430	370	12	30	52	BFS-250-25/25

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	300	20	490	430	16	30	52	BFS-300-20/25
18	300	25	490	430	16	30	60	BFS-300-25/25
19	350	20	585	490	16	33	60	BFS-350-20/25
20	350	25	585	490	16	33	68	BFS-350-25/25
21	400	20	640	550	16	36	68	BFS-400-20/25
22	400	25	640	550	16	36	74	BFS-400-25/25
23	500	20	735	660	20	36	80	BFS-500-20/25
24	500	25	735	660	20	36	90	BFS-500-25/25
25	600	20	850	770	20	39	95	BFS-600-20/25
26	600	25	850	770	20	39	105	BFS-600-25/25
27	700	20	960	875	24	42	105	BFS-700-20/25
28	700	25	960	875	24	42	120	BFS-700-25/25
29	800	20	1085	990	24	48	120	BFS-800-20/25
30	800	25	1085	990	24	48	130	BFS-800-25/25
31	900	20	1200	1090	28	48	130	BFS-900-20/25
32	900	25	1200	1090	28	48	145	BFS-900-25/25
33	1000	20	1320	1210	28	56	145	BFS-1000-20/25

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: EN1092 PN25



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	1000	25	1320	1210	28	56	160	BFS-1000-25/25
35	1200	20	1540	1420	32	56	170	BFS-1200-20/25

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

21-04-2026