

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: JIS B2220 16K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	150	10	305	260	12	25	22	BFS-150-10/16K
2	150	16	305	260	12	25	28	BFS-150-16/16K
3	150	20	305	260	12	25	30	BFS-150-20/16K
4	200	10	350	305	12	25	25	BFS-200-10/16K
5	200	16	350	305	12	25	35	BFS-200-16/16K
6	200	20	380	305	12	25	40	BFS-200-20/16K
7	250	10	430	380	12	27	35	BFS-250-10/16K
8	250	16	430	380	12	27	40	BFS-250-16/16K
9	250	20	430	380	12	27	44	BFS-250-20/16K
10	300	10	490	430	16	27	40	BFS-300-10/16K
11	300	16	490	430	16	27	48	BFS-300-16/16K
12	300	20	490	430	16	27	52	BFS-300-20/16K
13	350	10	540	480	16	33	44	BFS-350-10/16K
14	350	16	540	480	16	33	52	BFS-350-16/16K
15	350	20	540	480	16	33	60	BFS-350-20/16K
16	400	10	600	540	16	33	48	BFS-400-10/16K

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: JIS B2220 16K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	400	16	600	540	16	33	60	BFS-400-16/16K
18	400	20	600	540	16	33	68	BFS-400-20/16K
19	450	10	710	605	20	33	52	BFS-450-10/16K
20	450	16	710	605	20	33	68	BFS-450-16/16K
21	450	20	710	605	20	33	74	BFS-450-20/16K
22	500	10	735	660	20	33	60	BFS-500-10/16K
23	500	16	735	660	20	33	74	BFS-500-16/16K
24	600	10	844	770	24	39	68	BFS-600-10/16K
25	600	16	844	770	24	39	85	BFS-600-16/16K
26	600	20	850	770	24	39	95	BFS-600-20/16K
27	700	10	960	875	24	42	74	BFS-700-10/16K
28	700	16	960	875	24	42	92	BFS-700-16/16K
29	700	20	960	875	24	42	110	BFS-700-20/16K
30	800	10	1085	990	24	48	85	BFS-800-10/16K
31	800	16	1085	990	24	48	105	BFS-800-16/16K
32	800	20	1085	990	24	48	120	BFS-800-20/16K
33	900	10	1190	1090	28	48	95	BFS-900-10/16K

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Blind Flenzen

Matrix (hars) Vinylester (Derakane 411 of equivalent)

Drilling Standard: JIS B2220 16K



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	900	16	1190	1090	28	48	115	BFS-900-16/16K
35	1000	10	1320	1210	28	56	105	BFS-1000-10/16K
36	1000	16	1320	1210	28	56	130	BFS-1000-16/16K
37	1100	10	1430	1310	32	56	110	BFS-1100-10/16K
38	1100	16	1430	1310	32	56	140	BFS-1100-16/16K
39	1200	10	1540	1420	32	56	120	BFS-1200-10/16K
40	1200	16	1540	1420	32	56	155	BFS-1200-16/16K

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

21-04-2026